



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/735,576	12/12/2003	Gregory Robin Price	TRMB1471	2547
70409 7590 09/12/2008 TRIMBLE NAVIGATION LIMITED C/O WAGNER BLECHER 123 WESTRIDGE DRIVE WATSONVILLE, CA 95076				
EXAMINER TRAN, DALENA				
ART UNIT 3664		PAPER NUMBER		
MAIL DATE 09/12/2008		DELIVERY MODE PAPER		

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary

Application No.

10/735,576

Applicant(s)

PRICE ET AL.

Examiner

Dalena Tran

Art Unit

3664

Period for Reply -- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 27 June 2008.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-3,5-14, 16-30 and 32-35 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-3,5-14, 16-30, 32-35 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- 1) ☐ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☐ Information Disclosure Statement(s) (PTO/SB/06)
Paper No(s)/Mail Date _____
- 4) ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date _____
- 5) ☐ Notice of Informal Patent Application
- 6) ☐ Other: _____

**UNITED STATES DEPARTMENT OF COMMERCE****U.S. Patent and Trademark Office**

Address : COMMISSIONER FOR PATENTS

P.O. Box 1450

Alexandria, Virginia 22313-1450

APPLICATION NO./ CONTROL NO.	FILING DATE	FIRST NAMED INVENTOR / PATENT IN REEXAMINATION	ATTORNEY DOCKET NO.
10735576	12/12/03	PRICE ET AL.	TRMB1471

TRIMBLE NAVIGATION LIMITED C/O WAGNER BLECHER
123 WESTRIDGE DRIVE
WATSONVILLE, CA 95076

EXAMINER

Dalena Tran

ART UNIT	PAPER
----------	-------

3664

20080910

DATE MAILED:

Please find below and/or attached an Office communication concerning this application or proceeding.

Commissioner for Patents

DETAILED ACTION

Notice to Applicant(s)

1. This office action is responsive to the amendment filed on 6/27/08. Claims 1-3, 5-14, 16-30, and 32-35 are pending.

Claim Rejections - 35 USC § 103

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

3. Claims 1-3, 5-14, and 16-24, are rejected under 35 U.S.C. 103(a) as being unpatentable over Gvili (5,717,593), in view of Fowler et al. (6,104,979), McClure et al. (6,539,303), Murphy (6,711,475), and Weindorf (6,762,741).

As per claim 1, Gvili discloses an integrated guidance system comprising: a position determination system adapted for determining a current position (see at least column 5, lines 10-25), a lightbar device adapted for providing a visual representation of a deviation of current position from a desired path to guide movement along desired path (see at least columns 5-6, lines 40-56; and column 8, lines 1-57), and a processor adapted for facilitating user interaction by integrating operation of position determination system, lightbar device, data input device, and display device (see at least column 7, lines 29-67; and column 8, lines 18-57). Gvili does not explicitly disclose a display device for displaying text and graphics. However, Gvili discloses a system capable of displaying text and graphics, because Gvili discloses a map display (see at least column 7, line 49-52), and alphanumeric data (see at least column 7, lines 54-57), and the

indicator of alphanumeric capability, such as necessary to post the control prompt in text (see column 7, lines 10-13).

In addition, to modify for the teach of Gvili, Fowler et al. disclose a display device for displaying graphics (see at least the abstract; and columns 3-4, lines 66-30). Also, a text display is well known as teach by Murphy (see column 7, lines 1-55). Gvili discloses a data input device for selecting (see at least column 4, lines 10-17; column 6, lines 53-56; and column 7, lines 29-37). Gvili does not explicitly disclose a scrolling, and editing operations. However, Gvili discloses a control panel (72) in figure 1, has switch and arrow keys, enable for the pilot to make a selection (see column 6, lines 53-56). It would have been obvious to one of ordinary skill in the art that, the control panel (72) represent a mechanical input device capable of performing a scrolling, and editing operations through the arrow keys and select keys. Furthermore, to modify for the teach of Gvili, McClure et al. disclose a data input device for scrolling operations (see at least column 5, lines 46-47; and column 4, lines 20-28). In addition, also to modify for the teach of Gvili, Murphy discloses a data input device for editing operations (see at least columns 7-8, lines 1-45), including configuring position determining system with a menu, and display menu (see column 4, lines 42-54; and column 5, lines 31-56).

Furthermore, in claim 1, Gvili do not disclose a housing enclosing position determination system, lightbar device, data input device, display device, and processor. However, McClure et al. ('303) disclose a navigation guidance system to guide a vehicle to a desired path (see the abstract), and a housing enclosing position determination system, lightbar device, data input device, display device, and processor (see at least column 4, lines 20-38). Also, McClure et al. disclose the components of the system maybe incorporated into a single unit or maybe a separate

Art Unit: 3664

module (column 4, lines 30-35), when a component as a separate unit, it would be connected to the controller by a cable (see '303, column 4, line 37). It is well known in the art that when the system components are integrated into one single unit, the components are interconnected in signals communication with a serial communication bus and a controller, and one of ordinary skill in the art would understand that the cables connection will be eliminated, and instead a communication bus would allows a central controller to maintain control over all of the system components and regulate the signal traffic on the serial bus. Also, eliminate the use of cables connection, will have the benefit of reducing congestion in a small cockpit of a vehicle such as an aircraft.

In addition, in claim 1, McClure et al. also disclose a differential global position determination system adapted for using a differential correction process to correct errors, wherein a differential correction maybe stored in an electronic file and accessed later or may be applied in real time (see the abstract; column 4, lines 47-65; and columns 6-7, lines 5-11). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the teach of Gvili by combining a display device for displaying text and graphics for easily viewing and interacting by the user for providing navigation guidance; also, it would have been obvious to one of ordinary skill in the art to combine a data input device include scrolling, editing operations, configuring position determining system with a menu, and display menu so the user can manual select a desired parameter in a display screen with variety of different option selecting and editing data; and it would have been obvious to one of ordinary skill in the art by incorporated system components into a single unit enclosing into a housing for interconnecting and regulating the signals of relating system components, and to avoid overcrowd of obstacles

such as too many cables connect in a space constraint of a cockpit vehicle. Furthermore, the less of an obstacle blocking any portion of a cockpit space, the quicker and closer a pilot will be able to acquire and maintain the desired course line across a desired path, therefore, the safer the mission can be conducted; also, it would have been obvious to one of ordinary skill in the art to combine a differential global position determination system for steering correction the vehicle current track error or distance from the desired path.

Furthermore, in claim 1, Gvili does not disclose display adapted to be viewable under various light condition. However, Weindorf discloses text, menu, and graphics adapted to be viewable under various light conditions, wherein an operator is able to vary the contrast and brightness of text, menu, and graphics by using buttons to interact with a user interface of integrated guidance system (see columns 1-2, lines 30-20; column 3, lines 38-50; columns 5-6, lines 3-18; columns 6-7, lines 53-46; columns 9-10, lines 45-56; and column 15, lines 1-64). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the teach of Gvili by combining display adapted to be viewable under various light condition enabling a user to adjust the display device in a manner to suit one or more viewing preferences.

In addition, Gvili does not disclose the housing has a wing shaped portion. However, McClure et al. disclose an integrated guidance system with a square shaped (figure 2). It would have been well known, and it would have been obvious to one of ordinary skill in the art that one can design a housing enclosing a guidance system with many different shapes such as a T shaped, a L shaped, a wing or fan shaped, or a S shaped, it just a design choice, because depend on how electrical components inside is layout, a housing need to design a shape that can enclose the whole system components. It would have been obvious to one of ordinary skill in the art at the

time the invention was made to modify the teach of Gvili by combining different shaped of a housing enclosing an integrated guidance system depend on how the electrical link between various components inside the housing, in order to protect the electrical components, and therefore, the electrical connector or cable connector, and circuit board component will not vibrate or disengage relative to each other, in order to assist positioning of components, so as to enhance stability.

As per claims 2-3, Gvili discloses position determination system comprises a GPS antenna and a GPS receiver, GPS antenna is positioned externally and separately relative to GPS receiver (see at least column 5, lines 10-25).

As per claims 5-6, Gvili discloses lightbar device comprises a plurality of lights that are adapted to emit a light pattern that indicates deviation, wherein plurality of lights are spaced apart and are aligned in a row, and wherein light pattern is formed by selectively illuminating particular ones of plurality of lights (see at least column 8, lines 1-57).

As per claim 7, Gvili discloses plurality of lights comprises a plurality of LED's (see at least column 5, lines 26-40).

As per claims 8-9, Gvili does not disclose data input device comprises a first, second, and third button. However, Fowler et al. disclose data input device comprises a first, second, and third button, wherein first, second, and third buttons facilitate interacting with a plurality of available functions displayed on display device (see at least column 3, lines 40-60). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the teach of Gvili by combining data input device comprises a first, second, and third button for selecting different available option in the display device.

As per claim 10, Fowler et al. discloses display device displays available functions in a menu driven manner that is user friendly (see at least column 3, lines 20-40).

As per claim 12, Gvili discloses an integrated guidance system comprising: a position determination system adapted for determining a current position (see at least column 5, lines 10-25), and a lightbar device adapted for providing a visual representation of a deviation of current position from a desired path to guide movement along desired path (see at least columns 5-6, lines 40-56; and column 8, lines 1-57). Gvili does not explicitly disclose a display device for displaying text and graphics. However, Gvili discloses a system capable of displaying text and graphics, because Gvili discloses a map display (see at least column 7, line 49-52), and alphanumeric data (see at least column 7, lines 54-57), and the indicator of alphanumeric capability, such as necessary to post the control prompt in text (see column 7, lines 10-13). In addition, to modify for the teach of Gvili, Fowler et al. disclose a display device for displaying graphics (see at least the abstract; and columns 3-4, lines 66-30). Also, a text display is well known as teach by Murphy (see column 7, lines 1-55).

Gvili discloses a data input device for selecting (see at least column 4, lines 10-17; column 6, lines 53-56; and column 7, lines 29-37). Gvili does not explicitly disclose a scrolling, and editing operations. However, Gvili discloses a control panel (72) in figure 1, has switch and arrow keys, enable for the pilot to make a selection (see column 6, lines 53-56). It would have been obvious to one of ordinary skill in the art that, the control panel (72) represent a mechanical input device capable of performing a scrolling, and editing operations through the arrow keys and select keys.

Furthermore, to modify for the teach of Gvili, McClure et al. disclose a data input device for scrolling operations (see at least column 5, lines 46-47; and column 4, lines 20-28). In addition, also to modify for the teach of Gvili, Murphy discloses a data input device for editing operations (see at least columns 7-8, lines 1-45), including configuring position determining system with a menu, and display menu (see column 4, lines 42-54; and column 5, lines 31-56).

Furthermore, in claim 12, Gvili do not disclose a housing enclosing position determination system, lightbar device, data input device, and display device. However, McClure et al. ('303) disclose a navigation guidance system to guide a vehicle to a desired path (see the abstract), and a housing enclosing position determination system, lightbar device, data input device, display device (see at least column 4, lines 20-38). Also, McClure et al. disclose the components of the system maybe incorporated into a single unit or maybe a separate module (column 4, lines 30-35), when a component as a separate unit, it would be connected to the controller by a cable (see '303, column 4, line 37). It is well known in the art that when the system components are integrated into one single unit, the components are interconnected in signals communication with a serial communication bus and a controller, and one of ordinary skill in the art would understand that the cables connection will be eliminated, and instead a communication bus would allows a central controller to maintain control over all of the system components and regulate the signal traffic on the serial bus. Also, eliminate the use of cables connection, will have the benefit of reducing congestion in a small cockpit of a vehicle such as an aircraft. In addition, in claim 12, McClure et al. also disclose a differential global position determination system adapted for using a differential correction process to correct errors, wherein a differential correction maybe stored in an electronic file and accessed later or may be applied in real time

Art Unit: 3664

(see the abstract; column 4, lines 47-65; and columns 6-7, lines 5-11). Furthermore, in claim 12, Gvili does not disclose display adapted to be viewable under various light condition. However, Weindorf discloses text, menu, and graphics adapted to be viewable under various light conditions, wherein an operator is able to vary the contrast and brightness of text, menu, and graphics by using buttons to interact with a user interface of integrated guidance system (see columns 1-2, lines 30-20; column 3, lines 38-50; columns 5-6, lines 3-18; columns 6-7, lines 53-46; columns 9-10, lines 45-56; and column 15, lines 1-64). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the teach of Gvili by combining a differential global position determination system for steering correction the vehicle current track error or distance from the desired path; and also, it would have been obvious to combine a display adapted to be viewable under various light condition enabling a user to adjust the display device in a manner to suit one or more viewing preferences.

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the teach of Gvili by combining a display device for displaying text and graphics for easily viewing and interacting by the user for providing navigation guidance; also, it would have been obvious to one of ordinary skill in the art to combine a data input device include scrolling, editing operations, and configuring position determining system with a menu, and display menu so the user can manual select a desired parameter in a display screen with variety of different option selecting and editing data; and it would have been obvious to one of ordinary skill in the art by incorporated system components into a single unit enclosing into a housing for interconnecting and regulating the signals of relating system components, and to avoid overcrowd of obstacles such as too many cables connect in a space constraint of a cockpit

vehicle. Furthermore, the less of an obstacle blocking any portion of a cockpit space, the quicker and closer a pilot will be able to acquire and maintain the desired course line across a desired path, therefore, the safer the mission can be conducted.

In addition, Gvili does not disclose the housing has a wing shaped portion. However, McClure et al. disclose an integrated guidance system with a square shaped (figure 2). It would have been well known, and it would have been obvious to one of ordinary skill in the art that one can design a housing enclosing a guidance system with many different shapes such as a T shaped, a L shaped, a wing or fan shaped, or a S shaped, it just a design choice, because depend on how electrical components inside is layout, a housing need to design a shape that can enclose the whole system components. It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the teach of Gvili by combining different shaped of a housing enclosing an integrated guidance system depend on how the electrical link between various components inside the housing, in order to protect the electrical components, and therefore, the electrical connector or cable connector, and circuit board component will not vibrate or disengage relative to each other, in order to assist positioning of components, so as to enhance stability.

As per claims 13-14, Gvili discloses position determination system comprises a GPS antenna and a GPS receiver, GPS antenna is positioned externally and separately relative to GPS receiver (see at least column 5, lines 10-25).

As per claims 16-17, Gvili discloses lightbar device comprises a plurality of lights that are adapted to emit a light pattern that indicates deviation, wherein plurality of lights are spaced

apart and are aligned in a row, and wherein light pattern is formed by selectively illuminating particular ones of plurality of lights (see at least column 8, lines 1-57).

As per claim 18, Gvili discloses plurality of lights comprises a plurality of LED's (see at least column 5, lines 26-40).

As per claim 19, Fowler et al. discloses user interface system comprises a processor, and processor executable instructions for implementing a user interface (see at least columns 2-3, lines 49-19).

As per claim 20, Gvili does not disclose data input device comprises a first, second, and third button. However, Fowler et al. disclose data input device comprises a first, second, and third button (see at least column 3, lines 40-60). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the teach of Gvili by combining data input device comprises a first, second, and third button for selecting different available option in the display device.

As per claim 21, Fowler et al. discloses user interface system displays a plurality of available functions on display device (see at least columns 3-5, lines 64-22).

As per claims 22-23, Fowler et al. discloses first, second, and third buttons facilitate interacting with a plurality of available functions displayed on display device, and display device displays available functions in a menu driven manner that is user friendly (see at least column 3, lines 20-60).

As per claims 11, and 24, Gvili does not disclose LCD. However, McClure et al. disclose display device comprises a LCD (see at least column 5, lines 21-56). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the teach

of Gvili by combining display device comprises a LCD for displaying integrated guidance system.

4. Claims 25-27, and 35, are rejected under 35 U.S.C. 103(a) as being unpatentable over Fowler et al. (6,104,979) in view of McClure et al. (6,539,303), Murphy (6,711,475), and Weindorf (6762741).

As per claim 25, Fowler et al. disclose a method of interacting with a guidance system, method comprising: displaying on a display device of guidance system a plurality of available functions in a menu-driven manner that is user friendly, wherein display device display is adapted for displaying graphics (see at least the abstract; and columns 3-4, lines 66-30); and providing guidance system a data input device adapted for accessing and interacting with any one of available functions with a minimum number of inputs, and with minimum use of inputs (see at least column 3, lines 40-60), data input device enables selecting operations (see at least the abstract; column 1, lines 49-55; and columns 3-4, lines 50-30). Fowler et al. do not disclose a text display. However, Murphy discloses a text display (see column 7, lines 1-55). Fowler et al. also do not disclose a data input device for scrolling, and editing operations. However, McClure et al. disclose a data input device for scrolling operations (see at least column 4, lines 20-28; and column 5, lines 46-47). Also, Murphy discloses a data input device for editing operations (see at least columns 7-8, lines 1-59), including configuring position determining system with a menu, and display menu (see column 4, lines 19-37; and column 5, lines 35-56). Furthermore, in claim 25, Fowler et al. do not disclose a housing enclosing data input device, guidance system, and display device. However, McClure et al. ('303) disclose a navigation guidance system to guide a vehicle to a desired path (see the abstract), and a housing enclosing

Art Unit: 3664

data input device, guidance system, and display device (see at least column 4, lines 20-38).

Also, McClure et al. disclose the components of the system maybe incorporated into a single unit or maybe a separate module (column 4, lines 30-35), when a component as a separate unit, it would be connected to the controller by a cable (see '303, column 4, line 37). It is well known in the art that when the system components are integrated into one single unit, the components are interconnected in signals communication with a serial communication bus and a controller, and one of ordinary skill in the art would understand that the cables connection will be eliminated, and instead, a communication bus would allows a central controller to maintain control over all of the system components and regulate the signal traffic on the serial bus. Also, eliminate the use of cables connection, will have the benefit of reducing congestion in a small cockpit of a vehicle such as an aircraft.

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the teach of Fowler et al. by combining a display device for displaying text and graphics for easily viewing and interacting by the user for providing navigation guidance; also, it would have been obvious to one of ordinary skill in the art to combine a data input device include scrolling, editing operations, and configuring position determining system with a menu, and display menu so the user can manual select a desired parameter in a display screen with variety of different option selecting and editing d; and it would have been obvious to one of ordinary skill in the art that by incorporated system components into a single unit enclosing into a housing for interconnecting and regulating the signals of relating system components, and to avoid overcrowd of obstacles such as too many cables connect in a space constraint of a cockpit vehicle. Furthermore, the less of an obstacle blocking any portion of a cockpit space, the quicker

and closer a pilot will be able to acquire and maintain the desired course line across a desired path, therefore, the safer the mission can be conducted.

In addition, Fowler et al. do not disclose display adapted to be viewable under various light condition. However, Weindorf discloses text, menu, and graphics adapted to be viewable under various light conditions, wherein an operator is able to vary the contrast and brightness of text, menu, and graphics by using buttons to interact with a user interface of integrated guidance system (see columns 1-2, lines 30-20; column 3, lines 38-50; columns 5-6, lines 3-18; columns 6-7, lines 53-46; columns 9-10, lines 45-56; and column 15, lines 1-64). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the teach of Fowler et al. by combining a display adapted to be viewable under various light condition enabling a user to adjust the display device in a manner to suit one or more viewing preferences. In addition, Gvili does not disclose the housing has a wing shaped portion. However, McClure et al. disclose an integrated guidance system with a square shaped (figure 2). It would have been well known, and it would have been obvious to one of ordinary skill in the art that one can design a housing enclosing a guidance system with many different shapes such as a T shaped, a L shaped, a wing or fan shaped, or a S shaped, it just a design choice, because depend on how electrical components inside is layout, a housing need to design a shape that can enclose the whole system components. It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the teach of Gvili by combining different shaped of a housing enclosing an integrated guidance system depend on how the electrical link between various components inside the housing, in order to protect the electrical components, and therefore, the electrical connector or cable connector, and circuit board component will not

vibrate or disengage relative to each other, in order to assist positioning of components, so as to enhance stability.

As per claims 26-27, Fowler et al. disclose data input device comprises a first, second, and third input buttons (see at least column 3, lines 40-60. McClure et al. also disclose data input device comprises a first, second, and third input buttons (see at least column 4, lines 19-38; and column 5, lines 35-56).

As per claim 35, Fowler et al. do not disclose LCD. However, McClure et al. disclose display device comprises a LCD (see at least column 5, lines 21-56). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the teach of Fowler et al. by combining display device comprises a LCD for displaying integrated guidance system.

5. Claims 28-30, and 32-34, are rejected under 35 U.S.C. 103(a) as being unpatentable over in view of Fowler et al. (6,104,979), McClure et al. (6,539,303), Murphy (6,711,475), and Weindorf (6762741) as applied to claim 25 above, and further in view of Gvili (5,717,593).

As per claim 28, Fowler et al. disclose an integrated guidance system comprising: a position determination system adapted for determining a current position (see at least column 3, lines 40-60). Fowler et al. do not disclose a lightbar device. However, Gvili discloses a lightbar device adapted for providing a visual representation of a deviation of current position from a desired path to guide movement along desired path (see at least columns 5-6, lines 40-56; and column 8, lines 1-57). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the teach of Fowler et al. by combining a lightbar device for displaying a position and deviation from a guide path of the navigation system.

As per claims 29-30, Fowler et al. disclose GPS receiver (see at least column 3, lines 40-60). Fowler et al. do not disclose GPS antenna. However, Gvili discloses GPS antenna (see at least column 5, lines 10-25). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the teach of Fowler et al. by combining GPS antenna for accurately determine a position of the vehicle.

As per claims 32-33, Gvili discloses lightbar device comprises a plurality of lights that are adapted to emit a light pattern that indicates deviation, wherein plurality of lights are spaced apart and are aligned in a row, and wherein light pattern is formed by selectively illuminating particular ones of plurality of lights (see at least column 8, lines 1-57).

As per claim 34, Gvili discloses plurality of lights comprises a plurality of LED's (see at least column 5, lines 26-40).

Remarks

6. Applicant's arguments filed 6/27/08 have been fully considered but they are not persuasive.

In response to applicant's argument about "wing-shaped portion configured to protect a cable connector extending from housing" in the last paragraph page 10 of the amendment, the examiner recognizes that obviousness can only be established by combining or modifying the teachings of the prior art to produce the claimed invention where there is some teaching, suggestion, or motivation to do so found either in the references themselves or in the knowledge generally available to one of ordinary skill in the art. See *In re Fine*, 837 F.2d 1071, 5 USPQ2d 1596 (Fed. Cir. 1988) and *In re Jones*, 958 F.2d 347, 21 USPQ2d 1941 (Fed. Cir. 1992). In this case, it is the knowledge generally available to one of ordinary skill in the art that, "the

wing shaped portion” is just a design choice, because one can design a housing enclosing a guidance system with many different shapes such as a T shaped, a L shaped, a wing or fan shaped, or a S shaped, and depending on how electrical components inside is layout, a housing need to be designed a proper shape, so that can enclose the whole system components in order to protect the components inside the housing, because the system components can be damaged as the result of vibrate or disengage relative to each other, if the shape of the shape of the housing designed not enclose all the components inside. It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the teach of Gvili by combining different shaped of a housing enclosing an integrated guidance system depend on how the electrical link between various components inside the housing, in order to protect the electrical components, and therefore, the electrical connector or cable connector, and circuit board component will not vibrate or disengage relative to each other, in order to assist positioning of components, so as to enhance stability. These reasons have been provided in the last office action.

7. All the rejections and all the reasons for combining references are the same as in the last office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP 706.07(a).

Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136 (a).

A shorten statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE MONTHS shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136 (a) will

be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

8. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Dalena Tran whose telephone number is 571-272-6968. The examiner can normally be reached on M-W (in a first week of a bi-week), and T-R (in a second week of bi-week) from 7:00AM-6:00PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Khoi H. Tran can be reached on 571-272-6919. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Dalena Tran/
Primary Examiner, Art Unit 3664
September 10, 2008

